

BIOSENSE™ PA5B (GEN 2)

10" ANDROID BIOMETRIC TABLET

AMREL®
Pioneering Customized Rugged Solutions

Octa-core, Android 9 Mobile Biometric Tablet



Powerful 8-Core Mobile Biometric Tablet to Enroll & Capture Data

The 2nd generation of BioSense PA5B (Gen2) lets you enroll and capture biometric data wherever you are, whenever you want it. The newly overhauled model packs a punch with the best-performing Snapdragon 660 octa-core SoC, 3GB LPDDR4 RAM, 32GB eMMC storage, and runs on Android 9 (Pie).

Ideal for public safety officers, military personnel, border patrol agents, and other field operators, this MIL-STD 810G and IP-65 biometric tablet will operate even in the harshest conditions.

Android 9 (GMS-Certified)

System Integrators, developers, or other VARs whose app rely on Google Mobile Services (GMS) can now leverage Android 9 to achieve seamless flow and productivity. Not all applications require GMS to run,

but is a nice feature for those apps that are GMS-dependent.

Ultra-Fast Connectivity

The updated core hardware introduces newer technology with speedy connectivity options to transmit data captured in the field. Precise tracking, quick processing, wide coverage, and fast data transfer are supported by 802.11ac WiFi (supports 2x2 MU-MIMO; max 867 Mbps), Bluetooth 5, GNSS, and 4G LTE options.

Multiple Modular Options

Law enforcement professionals can select fingerprint scanners that are FBI-certified for FAP45 (flat and rolled). Also available are modules with capabilities for MSR, NFC, smart card (CAC), 2D barcode, and more.

SPECIFICATIONS | BioSense™ PA5B (Gen2) 10.1" RUGGED ANDROID™ BIOMETRIC TABLET

Operating System	Android 9.0 Google Mobile Services (GMS) certified	Sensor	Gyroscope, G-sensor, E-compass, Light sensor		
CPU	Qualcomm® Snapdragon™ 660 Octa-Core, 1.9GHz (up to 2.2GHz)	Power Adapter	AC 100V~240V, 50~60Hz Input; 19VDC@3.42A, 65W		
Memory	3GB LPDDR4 RAM	Battery	<ul style="list-style-type: none"> • Standard : 4500mAh, 10.8V, hot swappable battery Battery operation* : 13 hours • Extended (option): 9000mAh, 10.8V, hot swappable battery Battery operation* : 26 hours <p style="font-size: small; margin-top: 5px;">* The listed battery life is tested with wireless on. Actual performance will vary by configuration, application, and operating conditions.</p>		
Storage	32GB eMMC	I/O Interface	<ul style="list-style-type: none"> • USB 3.1 Type C x 1 (DP supported), USB 2.0 Type A x 2 • Gigabit ethernet (RJ-45) x 1 • RS-232 x 1 (trade-off option: USB 2.0 Type A) • Micro SD (SDXC/SDHC supported) x 1, Micro SIM x 2 • Audio jack (headphone/microphone combo) x 1 • RF pass-through connector for WLAN, GNSS, WWAN x 2 (Optional) • Docking connector (12-pin) x 1; DC-in x 1 		
Display	<ul style="list-style-type: none"> • 10.1" WUXGA (1920 x 1200), 1000 nits • Sunlight readable display; supports night and stealth mode • 10-point capacitive touch supports glove touch, water rejection, palm rejection, 2mm hard tip stylus • Gorilla Glass 	Dimensions and Weight	14" x 7.7" x 0.9" (35.56 x 19.5 x 2.3 cm) 3.09 lbs. (1.4 kg)		
Graphic	Qualcomm® Adreno™ 512	LED Indicator	<ul style="list-style-type: none"> • Power on/off • Wi-Fi on/off • Fn on/off • Battery full /charging/low 		
Control Button	<ul style="list-style-type: none"> • Programmable buttons x 3 • Barcode trigger x 1 • Power x 1, volume x 2, home button x 1 	Rugged Features	MIL-STD 810G IP-65 Certified 5-foot drop		
Communication	<ul style="list-style-type: none"> • Wi-Fi 802.11 ac 2x2 MU-MIMO • Bluetooth V5.0 (Class 1) • Optional 4G LTE • GNSS (GPS/GLONASS/BeiDou) 	Environment	<ul style="list-style-type: none"> • Operating temperature: -4° F to 140° F (-20° C to 60° C) • Storage temperature: -22° F to 158° F (-30° C to 70° C) • Humidity: 95%, non-condensing • Altitude, Thermal Shock, Shock, Transit Drop 		
Camera	<ul style="list-style-type: none"> • 8MP front camera • 13MP rear camera with LED flash 	Security	ARM® TrustZone®		
Data Collection	<ul style="list-style-type: none"> • FAP20 FBI PIV & Mobile ID FAP20 Single Fingerprint scanner • FAP45 FBI-certified fingerprint scanner (single/dual, flat or rolled prints) • FAP45 fingerprint scanner + MSR • NFC + Smart card reader (CAC) (Snap-on option) • 2D barcode reader (built-in option) 	Accessories	<table style="width: 100%; border: none;"> <tr> <td style="width: 50%; border: none;"> AVAILABLE: <ul style="list-style-type: none"> • Stylus Pen • Hand strap • Shoulder strap • Handle • Power adapter </td> <td style="width: 50%; border: none;"> OPTIONAL: <ul style="list-style-type: none"> • Vehicle Dock • Desktop Dock • Rugged Keyboard • VESA Mount Bracket • 4-bay Battery Charger • Long Life Battery Pack • Car Adapter </td> </tr> </table>	AVAILABLE: <ul style="list-style-type: none"> • Stylus Pen • Hand strap • Shoulder strap • Handle • Power adapter 	OPTIONAL: <ul style="list-style-type: none"> • Vehicle Dock • Desktop Dock • Rugged Keyboard • VESA Mount Bracket • 4-bay Battery Charger • Long Life Battery Pack • Car Adapter
AVAILABLE: <ul style="list-style-type: none"> • Stylus Pen • Hand strap • Shoulder strap • Handle • Power adapter 	OPTIONAL: <ul style="list-style-type: none"> • Vehicle Dock • Desktop Dock • Rugged Keyboard • VESA Mount Bracket • 4-bay Battery Charger • Long Life Battery Pack • Car Adapter 				

FINGERPRINT SCANNER SPECIFICATION

FBI PIV & Mobile ID FAP45 Fingerprint Sensor

Technology	Light Emitting Sensor (LES)
Resolution	500 PPI
Sensing Area	1.6" (W) x 1.5" (H)
Platen Area	3.38" x 2.12" 85.85 x 53.97 mm
Grayscale	256 grayscale dynamic range
Image Size	800 (W) x 750 (H) pixels
I/O Port	USB 2.0 (Pogo Pin, Molex 51146-0600, Molex 51021-0600)
Image Supported Formats	RAW, JPEG2000, BMP, PNG, WSQ
OS Support	Windows - Server, 7, 8.x, Mobile 6.5 Linux, Android 4.0 (or higher)
Certification	FCC Part 15 (per ANSI C62.4:2003) Class A, CSA ICES-003 Class A, CE Emissions: EN 55022:2006 Class A, CE Immunity EN 55024:1998/A1:2001/A2:2003, IEC 61000-4-2
Environment	Operating temperature: -10°C ~ +55°C / 14°F ~ 131°F Air & Contact Discharge, Humidity, Sufrace Durability, Vibration Test, Surface Resistance, Hazardous Material IP-65 Sealed bezel

** Specifications subject to change without notice **